

FLUIDMATIC G3 SYN



FLUIDMATIC G3 SYN is a superior quality synthetic blend formulated to provide service in a wide variety of automotive automatic transmission applications.

USES

**Automatic transmissions
Torque converters
Power steering systems**

Recommended for passenger car, trucks and power steering units for which the manufacturer recommends a DEXRON III or MERCON fluid.

PERFORMANCES

Meets the requirements of major manufacturers warranties requirements

- GM DEXRON III-G, III-H
- FORD MERCON, MERCON V
- CHRYSLER ATF+3, ATF+4
- AUDI / VW LT-71141
- BMW LA-2634, LT-71141
- HONDA / ACURA Z1
- HYUNDAI / KIA SP-II, SP-III
- MERCEDES
- ZF TE-ML 14B 16L
- MITSUBISHI SP, SP-II, SP-III
- NISSAN D-Matic, J-Matic
- TOYOTA / LEXUS T, T-II, T-III, T-IV
- ALLISON C3, C4
- DENNISON HF-O
- SUNDSTRAND
- VICKERS vane & piston pump tests
- VOITH COMMERCIAL
- ZF TE-ML 09

CUSTOMER BENEFITS

Better cold & high temperature properties and longer service life than conventional ATF

- Meets multiple manufacturer requirements.
- Excellent resistance to oxidation.
- Extended drain interval.
- Fuel saving.
- Very high viscosity index.
- Very low pour point.

CHARACTERISTICS

FLUIDMATIC G3 SYN	ASTM	Typical value
Volumetric mass, at 15°C	D4052	0.851
Color	Visual	Red
Viscosity, cSt at 40°C	D445	35.0
Viscosity, cSt at 100°C	D445	7.8
Viscosity Index	D2270	203
Viscosity, cP at -40°C	D2983M	10,600
Flash Point, °C	D92	175
Pour Point, °C	D97	-53

The characteristics shown are mean values.

TOTAL LUBRICANTS CANADA inc.
220 LAFLEUR
LASALLE (QC) H8R 4C9

FLUIDMATIC G3 SYN
DECEMBER 2008

This lubricant used according to our recommendations and for its designed application does not represent any particular risk. A safety data sheet in conformity with the legislation now current in NA is available from your local sales advisor.