

MULTIS COMPLEX RT



Grease



Extreme pressure and very sticking lithium complex grease.

APPLICATIONS

Superior EP grease
Heavy duty, Heavy loads

- **MULTIS COMPLEX RT** is designed for the lubrication various applications in all types of operating conditions, but particularly where the operation temperature is high and the use of conventional lithium greases is limited.
- **MULTIS COMPLEX RT** is a true multi purpose grease specially formulated for lubrication of loaded slide-ball and roller-bearings, wheel-bearings, universal joints, chassis and other industrial applications.

PERFORMANCES

- **MULTIS COMPLEX RT** contains ashless additives that ensure exceptional protection against oxidation and corrosion at high temperatures.
- The combination of extreme pressure synergic agents gives incomparable performances under heavy loads.

CHARACTERISTICS

MULTIS COMPLEX RT	ASTM Method	1	2
Product code	--	T406595	T406097
NLGI grade	--	1	2
NLGI Certification		GC-LB	GC-LB
Base oil viscosity in cSt at 40°C	D445	520	520
Base oil viscosity in cSt at 100°C	D2161	36	36
Drop Point in °F	D2265	500	550
Penetration in mm at 25°C 60 Strokes	D217	310-340	265-295
4 ball extreme pressure test in kg	D2596	265	265
Charge/wear index Kg	D2596	47	47
Timken OK load in kg	D2509	55	55
Appearance	-	Red	Red
Texture	-	Tacky	Tacky
Anti-Rust Test	D1743	Pass	Pass
4 ball wear test, scar in mm 40 kg	D2266	0.4	0.4
Recommended temperature range	--	-20°C to 177°C	-20 °C to 177°C

The typical characteristics mentioned represent mean values.

Recommendation

- Always avoid contamination of the grease by dust and/or dirt when applying.
- Preferably use a pneumatic pump system or cartridges.