



RUBIA LD 10W30

High performance lubricant for Gas & ULSD Diesel engines

USES

All industrial vehicles RUBIA LD is designed to meet the requirements of 2007 engines equipped with after-treatment systems. Answer the very severe technical constraints of the new Low-Sulfur Low-emission Diesel engines.

All types of services Adapted to the most severe servicing conditions: can be used in trucks, off highway diesel equipment, farm tractors, light trucks with diesel engines turbocharged or not for: transport, deliveries, stop & go, construction, harvesting...

Environment

Suits all types of diesel and gas engines, particularly ecological using Ultra Low Sulfur Diesel fuels.

PERFORMANCES

Specifications API CJ-4 / CI-4+ / SM / SL

Meet OEM Requirements ALLISON C-4/TO-2 VOLVO VDS-4
CAT ECF-3
CUMMINS CES 20081/20076/20071
DDC 7SE270
FORD M2C171-C/D GM 9985930
GLOBAL DHD1

CUSTOMER BENEFITS

Increased drain intervals High performance level insures safer and longer drains intervals
Use the same lubricant for all the diesel engines of your fleet.

Very high technical performance Significant improvement in wear protection, piston deposit control and oil consumption compared to API CI-4+. Exceptional anti-wear and anticorrosion properties.
Outstanding soot handling and oxidation control.
Excellent viscosity stability in operation.
Very high detergency and dispersion levels
High level of TBN insuring protection for both Low and ULSD Fuels.

CCS, cP @ -25°C	4700	Total Base No., (D2896)	10
Viscosity, cSt @ 100°C	11,2	Specific Gravity	0,870
Viscosity, cSt @ 40°C	77,3	Flash Point, °C	220
Viscosity Index	135	NOACK%	12
Pour Point, °C	-36		